



Distributed by: Norman Lamps, Inc.

• Product Data • LED Flat Panel JL-BPL22-M40W-CCT-VL

LED-FP22-Select 2 X 2 LED Ceiling Light

Specification	Specification Values	2 X 2 Size
Voltage Input - Universal	100VAC~277VAC <i>(Premium Integrated Universal Voltage Driver)</i>	
Wattage - Select	15W 20W 25W 30W 40W	
Lumens	1,950lm • 2,600lm • 3,250lm • 3,900lm • 5,200lm	
Color Temperature - Select	3,500k • 4,000k • 5,000k • 5,700k • 6,500k <i>(Kelvin • CTT)</i>	
C.R.I.	>83 Color Rendering @ 5,000k	
Viewing Angle & Optics	120° Degrees with Premium Backlit Optics & Diffuser Lens	
Dimmability	Continuous Dimming (0-10V)	
DLC Qualified	DLC 5.1 Premium™	
Life Hours	50,000	
IP Rating	IP40 • Suitable for Damp Locations	
Mounting Options	Suspended Frame Mount • Flush Mount	
Housing Material	Aluminum, Plastic & Acrylic	
Optical Design	LED Backlit Optical Power Beam Diodes	
Panel Dimensions	600mm X 600mm X 38mm	
Panel Weight	3.3 lbs.	
Box Packaging	4 LED Panels Per Box	
Box Weight & Dimensions	15 Pounds Per Box • Box dimensions 660mm X 660mm X 160mm	
Warranty Period	5 Year Limited Warranty <i>(From purchase date on invoice)</i>	



- Power Selectable x 5
- Color Temperature Selectable x 5
- 2' x 2' LED Panel Lighting
- Bright & Uniform Light Distribution
- Simple, Quick, and Easy Installation
- Slim & Lightweight by Design
- Cost Effective Retrofit or New Construction
- 25 Selectable Options all in One LED Panel
- Wall Switch - Color Temperature Control Function

Manufactured by: Xiamen Homestar Tech Company Limited
JL-BPL22-M40W-CCT-VL

Distributed by: Norman Lamps, Inc
Norman quick reference PN LED-FP22-SEL



USA Toll Free: 800-992-8020 | Email: sales@normanlamps.com | Website: normanlamps.com