

Norman Lamps, Inc.

"Distributing Light to the World"




LED Vapor Tight Fixtures

2'/4'/8' lengths



5VA housing

Lens and LED module board integrated



Top features

- Luminous part is integrated.
- 5VA housing, the highest classification in the UL94 Standard.
- Field-adjustable light output and CCT.
- 0-10V dimming.
- Internal installed low voltage sensor and EM solution available.
- Operating temp range -40°C/-40°F to 40°C /104°F when fixture is surface mounted.

Benefits You Need

- Thanks to the UL 5VA housing, wires can be connected directly inside of the housing without internal junction box or silicone conduit.
- Faster installation because the luminous part can be easily removed.
- Plug and play bi-level microwave motion sensor available at additional cost. Keilton IFS08ET



Specifications

UL Listing:
Suitable for wet locations.

UL 94:
5VA flame classification.

LEDs:
Long-life, high-efficacy, micro-power LEDs.

Lifespan:
Lumen Maintenance, L70 > 100,000 hours.

Dimming Driver:
Driver includes dimming control wiring for 0-10V dimming systems. The dim-to-off voltage threshold of optional 12V AUX integrated driver ranges from 0.1V to 0.5V.

Housing and lens :
Light gray Polycarbonate housing with stainless steel latches, frosted Polycarbonate lens.

Operating temp range

-40°C/-40°F to 45°C/113°F when fixture is suspended at least 18" from ceiling.

-40°C/-40°F to 40°C/104°F when fixture is surface mounted.

IESNA LM-79 & IESNA LM-80 Testing:

Ever-tie LED luminaires have been tested based on IESNA LM-79 and LM-80 by a third-party laboratory.

Mounting:

Surface mounting (wall, ceiling) by brackets and screws.




Chain or cable suspending mounting by using brackets and V-hooks.

Optional accessories:


- Surface mounting kit included (1 water joint, 2 brackets, 2 V-hooks, 2 screws, 2 plastic expansion anchor wall plugs, 4 shims for screws)
- Chain (purchased separately)
- Cable (purchased separately)

Dimensions and Weights

Length



Height and width



Available products:

VP-B-2FT/1L/NF/25/20/15W, 120-277V 3250-2600-1950lm

VP-B-4FT/1L/NH/30/25/18W, 120-277V 3900-3250-2340lm

VP-B-4FT/1L/NL/45/38/34W, 120-277V 5850-4940-4420lm

VP-B-8FT/1L/NL/90/75/65W, 120-277V 11700-9750-8450lm



Manufactured by Zhejiang Hengdian Tospo Co., Ltd.

Distributed by Norman Lamps, Inc. 1775 Wallace Ave. St. Charles, Illinois 60174

USA: 1-800-992-8020 • Website: normanlamps.com • Email: sales@normanlamps.com

